

SPECIFICATION SHEET

Commodity : Polyester Chips BOPET Film

Application : BOPET Film, Filament

Origin : Indonesia

Sales Specifications

Product: Polyethylene Terephthalate (PET) polymer

Sl. No	Property	Unit	Specifications	Test Equipment
1	Intrinsic Viscosity	dl/g	0.610 ± 0.01	IVI METHOD
2	Melting point	°C	254.0 ± 2.0	ASTM D 3418
3	Color L	APHA	55.0 ± 4.0	ASTM D 1925
4	Color b	APHA	3.0 ± 1.5	ASTM D 1925
5	Ash Content	ppm	500 ± 150	IVI METHOD
6	COOH Content	eq/10 ⁶	30 ± 6.0	IVI METHOD
7	Moisture content (when packed)	ppm	Max. 1000	ASTM D 3164
8	Chips Size (rectangular)	gr/100 Ea	2.3 ± 0.3	IVI METHOD

Packing : 1000KGS IN PP WOVEN JUMBO BAGS

Container Loading : 20MT (20BAGS) IN 1 X 20FT CONTAINER



Copyright Tesport 2020

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Tesport F.T. cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Adnan Kahveci Mah.
Sayaca Cad. Ekol Center
Kat 2 No:50 Beylikduzu
Istanbul - Turkey
Tel: +90 212 856 05 01
www.tesport.com
resin@tesport.com