

SPECIFICATION SHEET

Commodity	:Polyester Chips Textile Grade Flame Retardant		
Application	:Mineral Water Bottle		
Origin	:Taiwan		
分析項目 Test Item	單位 Unit	測試方法 Test Method	標準值 Standard Value
極限粘度 Intrinsic Viscosity	dl/g	ASTM D-2857	0.800±0.02
色值 L value(白度)		CNS 13584 L3235	82.5±3
色值 b value(黃度)		CNS 13584 L3235	-1.5±2
熔點 Melting Point	°C	CNS 13584 L3235	246.5±4
酸價 Carboxyl End Group	meq/kg	DU PONT 2-4	<30
含水率 Water Content	wt. %	KARL-FISHER	<0.2
乙醛 Acetaldehyde Content	ppm	ASTM F-2013	<1
酯粒形狀 Pellet shape	-	cylindrical	cylindrical
粒重 Pellet weight	g/100grains	LL 1143401-D3-303	1.60±0.2
備註 REMARK			
Packing	:1000KGS IN PP WOVEN JUMBO BAGS		
Container Loading	:20MT (20BAGS) IN 1 X 20FT CONTAINER		



Copyright Tesport 2020

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Tesport F.T. cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Adnan Kahveci Mah.
Sayaca Cad. Ekol Center
Kat 2 No:50 Beylikduzu
Istanbul - Turkey
Tel: +90 212 856 05 01
www.tesport.com
resin@tesport.com