

01 January 2019

SALES SPECIFICATIONS

ETHYLENE GLYCOL COMMERCIAL POLYESTER GRADE SPECIFIED MATERIAL: 000101205133

TEST ITEM	ETHYLENE GLYCOL COMMERCIAL POLYESTER GRADE
Purity, %wt, minimum	99.9
Diethylene Glycol, %wt, maximum	0.05
Acidity, ppm, maximum, as Acetic Acid	20
Iron, ppm, maximum	0.1
Chlorides, ppm, maximum	0.2
UV Transmit @ 220nm, %T, minimum	70
UV Transmit @ 275nm, %T, minimum	90
UV Transmit @ 350nm, %T, minimum	98
Water, %wt, maximum	0.05
Color, Platinum-Cobalt Units, maximum	5
Appearance	Pass

Typical values for Specific Gravity (20/20°C): 1.1151 – 1.1156

Typical values for Refractive Index at 20°C: 1.4305 – 1.4330

Typical values for Ash content: < 20ppm



Copyright Tesport 2020

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Tesport F.T. cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Adnan Kahveci Mah.
Sayaca Cad. Ekol Center
Kat 2 No:50 Beylikduzu
Istanbul - Turkey
Tel: +90 212 856 05 01
www.tesport.com
resin@tesport.com