

16 August 2019

## SALES SPECIFICATIONS

### ETHYLENE GLYCOL ANTIFREEZE GRADE SPECIFIED MATERIAL: 000101196459

TEST ITEM	METHOD	ETHYLENE GLYCOL ANTIFREEZE GRADE
Purity, %wt, minimum	BY DIFFERENCE	95.0
Diethylene Glycol, %wt, maximum	ASTM E2409	5.0
Acidity, ppm, maximum, as Acetic Acid	ASTM E2679	100
Water, %wt, maximum	ASTM E1064	0.5
Color, Platinum-Cobalt Units, maximum	ASTM D5386	25
Appearance	ASTM E2680	Pass

Typical values for Specific Gravity (20/20°C): 1.1130 – 1.1170



Copyright Tesport 2020

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Tesport F.T. cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Adnan Kahveci Mah.  
Sayaca Cad. Ekol Center  
Kat 2 No:50 Beylikduzu  
Istanbul - Turkey  
Tel: +90 212 856 05 01  
[www.tesport.com](http://www.tesport.com)  
[resin@tesport.com](mailto:resin@tesport.com)